

FT8X0DR Series

OT Systems

10-bit Digital 8-ch Video with 1 or 2 Reverse Data




The FT8X0DR series supports optical transmission of high-quality 10-bit PCM coded video with reverse data through one fiber either in multimode or singlemode.

It provides a cost-effective solution for the transmission of eight-channel video together with either one or two data channel(s). Either standalone or card module is available for different installation requirements.

Features

- Eight-channel non-compressed 10-bit digital video transmission
- No video degradation over max. operating distance
- Signal to noise ratio better than 65 dB
- Supports NTSC, PAL & SECAM video systems
- Gold plated BNC connector
- Supports one or two reverse data
- Supports multi-protocol data in RS232, RS422 & RS485(2 or 4-wire) Tri-state formats
- External access for data format selection via DIP switches
- Laser diode for optical transmission
- Optimum sensitivity for power budget concerns
- Excellent suppression of EMI & RFI and elimination of ground loop
- Adjustment and maintenance free
- No setup just plug-and-play
- Hot-swappable card modules
- Duplicated LED indicators on the front and rear of the unit for the convenience of observation
- Transient voltage protection on power supply and all signal inputs & outputs
- Robust design for harsh environment applications
- Standalone or card module

Typical Application



10-bit Digital Video

FT8X0DR Series

Ordering Information

Model	Description	No. of Fibers (Wavelengths)	Optical Power Budget	Max. Distance
MULTIMODE (62.5/125 um)				
FT810DR-SMT FT810DR-SMR	8 Video Transmitter/1 Data Receiver 8 Video Receiver/1 Data Transmitter	1 (1310/1550 nm)	23 dB	1 km
FT820DR-SMT FT820DR-SMR	8 Video Transmitter/2 Data Receiver 8 Video Receiver/2 Data Transmitter			
SINGLEMODE (9/125 um)				
FT810DR-SST FT810DR-SSR	8 Video Transmitter/1 Data Receiver 8 Video Receiver/1 Data Transmitter	1 (1310/1550 nm)	17 dB	40 km
FT820DR-SST FT820DR-SSR	8 Video Transmitter/2 Data Receiver 8 Video Receiver/2 Data Transmitter			
FT810DR-SSTL FT810DR-SSRL	8 Video Transmitter/1 Data Receiver 8 Video Receiver/1 Data Transmitter	1 (1310/1550 nm)	24 dB	60 km
FT820DR-SSTL FT820DR-SSRL	8 Video Transmitter/2 Data Receiver 8 Video Receiver/2 Data Transmitter			
Accessories:	FT-C18. 19" rack mount chassis (purchased separately) for housing card modules FT-PA/12V. 12VDC power adapter included for standalone (US, European, UK or Australian power plug)			
Options:	Model numbers specified above are for Card Modules, please add ' SA ' for Standalone. eg. FT810DR-SMT SA ST type connector is standard. For FC type, specify ' F ' in the model number. Eg. FT810DR- F MT			

- NOTES: (1) Transmission distance will suffer if additional losses are introduced by the optical connectors, fusions, splices and the fibers within the network.
 (2) Operating distance of multimode is limited by the characteristics of the fiber bandwidth.
 (3) Power adaptor is manufactured by third party and is supplied with fitted screw-terminal output cables.
 (4) Please feel free to consult factory for any special requirement and customization

Specifications

Video		Connectors	
No. of Channels:	8	Optical:	ST (standard), FC
Bandwidth:	6.5MHz per channel	Video:	BNC
Format:	PAL / NTSC / SECAM	Data:	7-pin screw terminal
Input / Output:	1.0 Vp-p, 75 ohms	Power:	SA: 2-pin screw terminal Card: Futurebus connector
Differential Gain:	< 1% typical	Electrical and Mechanical	
Differential Phase:	< 1° typical	Power:	SA: 12VDC @ 6.0W Card: From FT-C18 chassis
Signal-to-Noise Ratio:	> 65dB	Dimensions (HxWxD):	SA: 50 x 156 x 212mm Card: 154 x 41 x 212mm
Data		Weight:	SA: 0.97kg Card type: 0.45kg
No. of Channels:	1	No. of rack slots:	2
Data Direction:	Reverse	LED Indicators:	Power, Video per channel, Optical carrier detected, Data Tx & Rx
Data Interface:	DIP switch-selectable RS232, RS422, RS485(2 or 4-wire) Tri-state	Environmental	
Data Format:	MPD (Manchester, Bi-phase, etc)	Operating Temp.:	-40°C to +75°C
Data Rate:	0~256Kbps	Storage Temp.:	-40°C to +85°C
		Relative Humidity:	0 to 95% non-condensing
		MTBF:	> 100,000 hours



**Lifetime
Warranty**