

## VR-C2190H

### 1.3 Megapixel IP Network PTZ Dome

Specification	
<b>Camera</b>	
Image sensor	1/3" Progressive Scan CCD
Effective pixel	1280(H) x 960 (V)
Minimum illumination	Color: 0.5 lux@F1.6, B/W:0.02 lux@F1.6
White balance	Auto/ Semi-auto/ manual/ ATW
AGC	Auto/ manual
S/N ratio	more than 50dB
BLC	On/ off
WDR	128X
Shutter	1/25~ 1/10,000s
Day & night	Automatically removable infrared-cut filter
Digital zoom	12x
Focus mode	Auto/ semi-auto/ manual
Privacy mask	Up to 4 masks
<b>Lens</b>	
Focal length	4.7- 84.6mm, 18x optical zoom
Zoom speed	Approx. 2s (optical Wide- Tele)
Angle of view	55.2~ 3.2° (Wide- Tele)
Min. working distance	10~ 1,500mm (Wide- Tele)
Aperture range	F1.6~ F2.8
<b>Pan &amp; Tilt</b>	
Pan range	360° endless
Pan speed	Manual pan speed: 0.2°- 300°/s, preset pan speed: 400°/s
Tilt range	0°- 90° (auto flip)
Tilt speed	Manual tilt speed: 0.5°- 90°/s, preset tilt speed: 150°/s
Proportional zoom	Rotation speed is adjusted automatically according to zoom ratio
Number of preset	256
Patrol	8 patrols, up to 32 presets per patrol
Patten	4 patterns, with total recording time not less than 10 min
Power loss recovery	Support
Park action	Preset/ patrol/ pattern/auto scan/ random scan/ frame scan/ panoramo scan
PTZ position display	On/ off
Freeze frame	On/off
Scheduled task	Preset/ patrol/ pattern/ pan scan/ tilt scan/ random scan/ frame scan/ panorama scan



#### Key Features:

- Up to 25 fps @ 720P (1280 × 720) resolution
- Up to 18x optical zoom
- Supports ONVIF and PSIA Standard
- Standard H.264 video compression
- Progressive scan CCD
- Built-in SD/SDHC Card Slot for On-board Storage
- Removable IR-cut Filter for True Day & Night Function
- Support dual streams
- Auto iris, electronic shutter for different environment
- Powerfull PTZ control, alarm and so on
- IP66 rating

#### Accessories: